

# 9100



*9100 in  
bayou bronze  
with backlit  
topper*

The 9100 is our best selling ATM. This extremely popular machine was designed to be a low cost high-performance ATM. And it has proven to be perfectly suited for owners who need functionality and performance at a lower price point.

*The most cost-effective ATM  
in the industry, bar none.*

The 9100 delivers Triton's unparalleled reliability and offers a number of additional features designed to maximize uptime, such as automatic error recovery. The 9100 also features Triton's own TDM-100 dispensing mechanism, which incorporates state-of-the-art electronics and a host of features including locking cassette.

And even though the 9100 features a low cost of ownership, it still incorporates many of the industry's tightest security features, such as VISA Encrypting PIN Pad (VEPP) and Triple DES, the new standard for PIN encryption.

Dollar for dollar, Triton's 9100 is simply the most cost-effective ATM in the industry, bar none.

# 9100 IN DETAIL

*The most cost-effective ATM in the industry, bar none.*

## FEATURES:


- Available in Blue and Bayou Bronze
- Single and multiple cassette options
- Trade-up Program
- 5.7" (145 mm) monochrome or color LCD transaction screen
- 60 mm thermal printer
- 14.4k baud modem or 33.6k baud modem
- Manual combination lock or electronic lock
- Dip-style card reader
- Small footprint
- Dimensions
  - 16" wide (405 mm)
  - 16"-20" deep (405mm-508mm) depending on dispenser options
  - 49" high (1245 mm) *without topper*
  - 60" high (1524 mm) *with topper*
- 126 lbs. (57 kg)
- UL 291 Business Hours Service cabinet

- Dial-up, or optional TCP/IP communications
- VISA Encrypting PIN Pad (VEPP) to comply with international encryption standards, Triple DES compliant
- Backlit graphic topper option
- Triton Connect™ compatible
- Advertising revenue potential:
  - Decal and signage
  - Couponing
  - Transaction screen
- Americans with Disabilities Act (ADA) and Audio compliant

## OPERATING SPECS:

- Temperature 10°- 30° C / 50°- 86° F
- Relative humidity 20%-80% non-condensing
- Power Consumption 2.0A @ 115 VAC at 60 Hz  
1.0A @ 230 VAC at 50 Hz

## ATM INSTALLATION SPACE REQUIREMENTS FOR ADA COMPLIANCE



*The dimensions shown comply with US Federal ADA guidelines. For installation within the US, be sure to check state and local guidelines for complete compliance. For non-USA installations, check regulations for the country in which the machine will be installed.*

*\*specifications subject to change without notice*



*9100 in bayou bronze with backlit topper*

Triton Headquarters • 522 East Railroad Street  
Long Beach, Mississippi 39560 USA  
With offices throughout the U.S. and worldwide including Canada, UK, Australia, and Hong Kong  
Phone: 1-228-868-1317 • Toll free: USA & Canada 1-800-367-7191  
www.triton.com • Email: sales@trtn.com



© 2006 Delaware Capital Formation, Inc. All Rights Reserved. TRITON, TRITON WHERE MONEY COMES FROM, DOVER and DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.